

**AMENDMENTS TO THE CLAIMS**

1. (Withdrawn) In an assembly cooperating upon the erection thereof to provide an adjustable mount for supporting a satellite dish antenna defined by a generally hollow base container including an upper and lower surface joined at the common peripheries thereof and including a keyed central annulus therebetween, a cylindrical segment conformed for receipt of one end thereof in said annulus and including a mounting post at the other end engaged by a manually operable pivot for selecting the alignment of said post relative said segment, said pivot including a perforated cap secured to said other end of said segment, a generally hemispherical threaded fitting retained within the common interior of said cap and segment, a helical spring for urging said fitting against said cap, a threaded projection extending from said post through the perforation in said cap and threadedably passing through said fitting and opposing means fixed in said segment for opposing said spring and further threaded advancement of said projection; and level indicating means secured to said mounting post, the improvement comprising: said lower surface of said base including a plurality of legs for the support thereof, each said leg being provided with a corresponding flexible loop conformed for sliding deployment from a stored position subjacent said lower surface of said container to an extended position exterior of the common periphery thereof.

2. (Withdrawn) Apparatus according to Claim 1, wherein:  
said one end of said segment and the interior of said annulus are each tapered at various angles of taper.

3. (Withdrawn) Apparatus according to Claim 2, wherein:

said upper and lower surface of said hollow base container are each of a generally triangular planform separated from each other to define a cavity therebetween and joined at the common peripheries thereof.

4. (Currently Amended) In a deployable assembly of cooperating parts conformed to provide upon the erection thereof an adjustable mount for supporting a satellite dish antenna on top of a generally triangular marine dock storage container, and including a cylindrical segment provided with a mounting post at one end conformed to be attached to said satellite dish and engaged by a manually operable pivot ~~for selecting the alignment of said post relative said segment~~ and level indicating means secured to said mounting post, the improvement comprising: a base including a generally triangular base plate provided with an annulus conformed for receiving the other end of said segment, a plurality of legs for supporting said base plate on said storage container, a plurality of securing perforations formed along the peripheral edge of said base plate and a corresponding plurality of elastic attachment straps for securing said base plate to said dock storage container.

5. (Original) Apparatus according to Claim 4, wherein:

the other end of said segment and the interior of said annulus are each tapered at various angles of taper.

6. (Original) Apparatus according to Claim 5, wherein:

each said leg is deployed subjacent a corresponding apex of said base plate and each said

securing perforation is formed along the periphery of said base plate intermediate said legs.

7. (Withdrawn) In a deployable assembly of cooperating parts conformed to provide upon the erection thereof an adjustable mount for mounting a satellite dish antenna onto a selected structural member of a recreational vehicle, and including a cylindrical segment provided with a mounting post at one end conformed to be attached to said satellite dish and engaged by a manually operable pivot for selecting the alignment of said post relative said segment and level indicating means secured to said mounting post, the improvement comprising: a clamping adapter conformed for clamped engagement to said selected structural member including a pair of opposed clamping pieces defining a common cavity therebetween for securing to one portion of said selected structural member; a first and second threaded fastener extending through said opposed clamping pieces; and a securing piece provided with a plurality of threaded opening pairs each spaced for threaded engagement by said first and second fasteners, said securing piece further including a transverse opening dimensioned for receipt of the other end of said cylindrical segment.

8. (Withdrawn) Apparatus according to Claim 7, wherein: said transverse opening is split along one radius thereof said split including adjustable bridging means thereacross.

9. (Withdrawn) Apparatus according to Claim 7, wherein:  
the other end of said segment and the interior of said transverse opening are each tapered  
at various angles of taper.
10. (New) A mount for an antenna comprising:  
a base having a tapered wall defining a cavity and a threaded portion located below the  
tapered wall;  
a pole having a first end that is tapered to mate with the tapered wall and that screws into  
the threaded portion and a second end; and  
a pivot structure connected with the second end.
11. (New) The mount of claim 10 further comprising a sleeve coupled with the pivot  
structure and having a knob to adjust an inner diameter of the sleeve.
12. (New) The mount of claim 10 further comprising a clamp coupled with the sleeve  
and a satellite dish.
13. (New) The mount of claim 10 further comprising at least three legs coupled with the  
base.
14. (New) The mount of claim 10 further comprising a plurality of cables each having a  
first end attached to the base and a second end terminated in an eyelet.
15. (New) The mount of claim 10 wherein the base is composed of a polymeric  
material.

16. (New) The mount of claim 10 further comprising a magnetic compass coupled with the base.

17. (New) A satellite dish mount comprising:  
a base having a top portion with an interior ring that defines a chamber with a threaded portion for receiving an attachment, and a bottom portion;  
a compass coupled with the base;  
a level coupled with the base; and  
an attachment means for securing the base.

18. (New) The satellite dish mount of claim 17 further comprising an attachment that mates with the chamber and is coupled to a satellite dish.

19. (New) The satellite dish mount of claim 17 further comprising an azimuth measuring means that measures the azimuth of the satellite dish.

20. (New) The satellite dish mount of claim 17 wherein the base is composed of a polymeric material.